

# IG PANEL PROGRAM DETAILS



	7/8" RLT-Top	7/8" Tilt	7/8" Custom	1" Custom	1" Classic
<b>IG WIDTH RANGES</b>	15" – 54" wide	8" – 54" wide	8" – 48" wide	8.625" – 80" wide	14" – 36" wide
<b>IG HEIGHT RANGES</b>	12" – 41" tall	12" – 68" tall	18" – 80" tall	13" – 80" tall	42" – 80" tall
<b>IG THICKNESS</b>	7/8" thick	7/8" thick	7/8" thick	1" thick	1" thick
<b>MAXIMUM SQ FT</b>	9	9	18	17	17
<b>GLASS TYPE</b>	Tempered or Annealed glass (single operator)	Tempered or Annealed glass (single operator)	Tempered glass up to 18 sq. ft. (dual operator 48" or greater)  Annealed glass up to 15 sq. ft. (single operator 48" or less)	Tempered glass up to 17 sq. ft. (single or dual operator 48" or greater)  Annealed glass up to 15 sq. ft. (single or dual operator 48" or less)	Tempered glass only (dual operator)
<b>LOW-E OPTIONS</b>	Single: 270, 272, 340, 366 Dual: I89/270, I89/272, I89/340, I89/366	Single: 270, 272, 340, 366 Dual: I89/270, I89/272, I89/340, I89/366	Single: 270, 272, 340, 366 Dual: I89/270, I89/272, I89/340, I89/366	Single: 270, 272, 340, 366 Dual: I89/270, I89/272, I89/340, I89/366	Single: 270, 272, 340, 366 Dual: I89/270, I89/272, I89/340, I89/366
<b>GLASS COATING</b>	NEAT: 270, 366, I89/270, I89/366	NEAT: 270, 366, I89/270, I89/366	NEAT: 270, 366, I89/270, I89/366	NEAT: 270, 366, I89/270, I89/366	N/A
<b>OPERATOR OPTIONS</b>	Top center operator position IG only  EasyGlide design 0.512" thickness	Upper right corner operator position IG only  Tilt design 0.629" Thickness	High or low operator position  Left or right-hand operator  EasyGlide design 0.539" thickness	High or low operator position  Left or right-hand operator  EasyGlide design 0.539" thickness SlimLine design* 0.323" thickness	Classic design 0.667" thickness  Left or right-hand operator  Low profile design 0.438" thickness
<b>BLIND COLOR</b>	White, Tan, Sand, Espresso, Silver Moon, Slate Gray	White, Tan, Sand, Espresso, Silver Moon, Slate Gray	White, Tan, Sand, Espresso, Silver Moon, Slate Gray	White, Tan, Sand, Espresso, Silver Moon, Slate Gray	White
<b>MINIMUM QUANTITY</b>	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1
<b>WORKING DAYS TO DELIVER</b>	Annealed: 8 business days + transit*  Tempered: 12 business days + transit*	Annealed: 8 business days + transit*  Tempered: 12 business days + transit*	Annealed: 8 business days + transit*  Tempered: 12 business days + transit*	Annealed: 8 business days + transit*  Tempered: 12 business days + transit*	Tempered: 12 business days + transit*
<b>10 YEAR FULL WARRANTY</b>	✓	✓	✓	✓	✓

\* SlimLine Operator available in white  
 + Widths below 10" will have an asymmetrical design  
 • See size chart for limitations



WARNING!  
 Cancer and Reproductive Harm -  
[www. P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)